
frost DRAINAGE

Product Specification





Name
Frost Floor drain assembly medium duty cast iron grating circular, medium sump body cast iron vertical outlet 110mm DIA

Code
31.0117

Description
Frost floor drain with 200mm circular flat grating, medium sump body and spigot outlet.
Supplied with membrane clamp.
Connect directly to pipework.
Untrapped medium duty assemblies for use in floors with an asphalt or composition surface membrane and subject to light vehicular traffic.

Cast iron Grade EN-GJL-150 to BS EN 1561:1997
80%-97% recycled materials
100% recyclable

Ductile iron BS EN 1563 & 1564
Greater than 80% recycled materials
100% recyclable

Body Material
CAST IRON

Body Type
UNTRAPPED

Grating Material
DUCTILE IRON

Flow Rate
N/A

Outlet Type
SPIGOT

Load Rating
L15 To BS EN 1253-1:2015

Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.