


# Product Specification





### Name

Frost Floor drain assembly medium duty cast iron grating circular, medium sump body cast iron vertical outlet 4" BSP

### Code

31.0094

### **Description**

Frost floor drain with 200mm circular flat grating, medium sump body and threaded outlet.
Supplied with membrane clamp.
Connect to pipework using an adaptor.
Untrapped medium duty assemblies for use in floors with an asphalt or composition surface membrane and subject to light vehicular traffic.

Cast iron Grade EN-GJL-150 to BS EN 1561:1997 80%-97% recycled materials 100% recyclable

Ductile iron BS EN 1563 & 1564 Greater than 80% recycled materials 100% recyclable

## **Body Material**

CAST IRON

# Body Type UNTRAPPED

# **Grating Material**

**DUCTILE IRON** 

### **Flow Rate**

N/A

### **Outlet Type**

**THREADED** 

### **Load Rating**

L15 To BS EN 1253

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.