



### Name

Frost Floor drain assembly medium duty th clamp  
fixed grating 240mm round, large sum body cast iron  
vertical outlet BSP6

### Code

31.0146

### Description

Frost floor drain with 240mm circular flat grating, large  
sump body and threaded outlet size BSP 6  
Supplied with membrane clamp.  
Connect to pipework using an adaptor.  
Untrapped medium duty assemblies for use in floors  
with an asphalt or composition surface membrane  
and subject to light vehicular traffic.

Cast iron Grade EN-GJL-150 to BS EN 1561:1997  
80%-97% recycled materials  
100% recyclable

Ductile iron BS EN 1563 & 1564  
Greater than 80% recycled materials  
100% recyclable

### Body Material

CAST IRON

### Body Type

UNTRAPPED

### Grating Material

DUCTILE IRON

### Flow Rate

N/A

### Outlet Type

THREADED

### Load Rating

L15 To BS EN 1253

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the  
pipe spigot & female thread within the roof  
outlet body. Using a flat spreading utensil,  
evenly spread the silicone into the threaded  
grooves. Insert the male into the female thread  
of the roof outlet body then carefully turn  
clockwise ensuring the thread is not "cross  
threading". Once fully tightened clean off  
excess silicone to both ends of the threaded  
connection.