


# Product Specification





#### Name

Frost Cold Roof drain assembly - fixed dome 220mm circular, large sump body with clamp, vertical threaded outlet 6" BSP

#### Code

33.0066

### **Description**

Frost Cold Roof drain assembly, medium-duty with fixed 220mm circular dome, large sump body and vertical threaded outlet size 6" BSP Supplied with body and clamp.

Domed rainwater outlets are suited to cold roof construction where the waterproof membrane is located on top of the roof deck.

Cast Iron Grade EN-GJL-150 to BS EN 1561:1997 80%-97% recycled materials 100% recyclable

Polycarbonate dome

## Body Material

CAST IRON

## **Grating Material**

POLYCARBONATE

## **Outlet Type**

**THREADED** 

### **Body Type**

N/A

#### **Flow Rate**

14.01

### **Grating Type**

**DOMED** 

## Load Rating

N/A

#### **Threaded Joint Instructions**

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.