





### Name

Frost Warm Roof drain assembly - fixed dome 220mm circular, large sump body with clamp, vertical threaded outlet 4" BSP

#### Code

33.0124

## **Description**

Frost Warm Roof drain assembly, medium duty with fixed circular dome 220mm, medium sump body and vertical threaded outlet size 4' BSP.

Supplied with body and clamp.

Rainwater outlets with domed gratings are suited to warm roof construction where the waterproof membrane is located above the insulation layer on top of the roof deck.

Cast Iron Grade EN-GJL-150 to BS EN 1561:1997 90%-97% recycled materials 100% recyclable

Polycarbonate dome

**Body Material** 

**CAST IRON** 

**Body Type** N/A

**Grating Material** 

**POLYCARBONATE** 

**Flow Rate** 

10.70

**Outlet Type** 

**THREADED** 

**Grating Type** 

DOMED

# **Load Rating**

N/A

### **Threaded Joint Instructions**

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.