
frost

Product Specification





Name

Frost Floor drain 150mm circular nickel bronze grating with medium sump body and threaded outlet size 4" BSP

Code

31.0451

Description

Frost floor drain assembly with height adjustable 150mm circular nickel bronze grating, medium sump body and threaded outlet. Membrane clamp & collar are an optional extra, 31.2030. Can be trapped using a removable trap (31.9510). Quick and easy to install Maintenance free and durable Can be connected to all types of pipework in general use, using adaptors. Nickel bronze for use in areas where they contribute to the aesthetic appeal of an area. Nickel Bronze BS1400 Creator than 80% recycled material

Greater than 80% recycled material 100% recyclable

Cast iron Grade EN-GJL-150 to BS EN 1561:1997 80-97% recycled materials 100% recyclable Body Material CAST IRON Body Type UNTRAPPED

Grating Material NICKEL BRONZE Flow Rate

Outlet Type

THREADED

Load Rating

L15 To BS EN 1253

Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.

Frost Drainage Ltd 01420 555572

sales@frostdrainage.com

frostdrainage.com