
# frost

# Product Specification





#### Name

Frost Floor drain 150mm square stainless steel grating 3mm slots with medium sump body and threaded outlet size 4" BSP

Code

31.0485

### Description

Frost floor drain assembly with height adjustable Slimline Heel Proof 150mm square stainless steel slotted grating, medium sump body and threaded outlet.

Membrane clamp & collar are an optional extra (31.2030). Can be trapped using a removable trap (31.9510).

Quick and easy to install

Maintenance free and durable

Connect body to all types of pipework in general use, using adaptors.

Stainless steel for use in areas where they contribute to the aesthetic appeal of an area.

Stainless Steel BS EN 10088-1:2005 Grade 1.4301 (304) or (316) if specified Average recyclable content 75%-85%

Cast iron Grade EN-GJL-150 to BS EN 1561:1997 80-97% recycled materials

Frost Drainage Ltd 01420 555572

Body Material CAST IRON Body Type UNTRAPPED

**Grating Material** STAINLESS STEEL Flow Rate

## Outlet Type

THREADED

### Load Rating

L15 To BS EN 1253

#### **Threaded Joint Instructions**

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.

sales@frostdrainage.com

frostdrainage.com