



## Name

Frost Floor drain 200mm circular ductile iron grating with large trapped sump body and threaded outlet size 4" BSP

## Code

31.0967

## Description

Frost floor drain assembly with height adjustable 200mm circular ductile iron grating, large trapped sump body and threaded outlet.

Membrane clamp & collar are an optional extra (31.2030).

Maintenance free and durable

Connect body to all types of pipework in general use, using adaptors.

Ductile iron is best suited for use in unfinished and/or industrial settings.

Ductile Iron BS EN 1563 & BS EN 1564

Greater than 80% recycled material

100% recyclable

Cast iron Grade EN-GJL-150 to BS EN 1561:1997

80-97% recycled materials

100% recyclable

## Body Material

CAST IRON

## Body Type

TRAPPED

## Grating Material

DUCTILE IRON

## Flow Rate

N/A

## Outlet Type

THREADED

## Load Rating

L15 To BS EN 1253

## Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.