



### Name

Frost Floor drain 150mm square stainless steel grating 3mm slots with large trapped sump body and threaded outlet size 4" BSP

### Code

31.0985

### Description

Frost floor drain assembly with height adjustable Slimline Heel Proof 150mm square stainless steel slotted grating, large trapped sump body and threaded outlet.

Membrane clamp & collar are an optional extra (31.2030).

Quick and easy to install

Maintenance free and durable

Connect body to all types of pipework in general use, using adaptors.

Stainless steel for use in areas where they contribute to the aesthetic appeal of an area.

Stainless Steel BS EN 10088-1:2005  
Grade 1.4301 (304) or (316) if specified  
Average recyclable content 75%-85%

Cast iron Grade EN-GJL-150 to BS EN 1561:1997  
80-97% recycled materials  
100% recyclable

### Body Material

CAST IRON

### Body Type

TRAPPED

### Grating Material

STAINLESS STEEL

### Flow Rate

N/A

### Outlet Type

THREADED

### Load Rating

L15 To BS EN 1253

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.