

June 2024

MetroDrain



MetroDrain pipes are used to collect and dispose of surface and sub-surface storm water. Perfectly designed for environmental water management, MetroDrain products can be used with pumps and sampling chambers, catchpits, soakaways, manholes and storm water attenuation systems.

| | |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material | High-density polyethylene (HDPE), |
| Colour | Available with a black corrugated outer wall and a green smooth inner wall. |
| Quality System & Inspection | All quality systems and inspection procedures comply with BS EN ISO 9001: 2015 (Certificate No: FM 01420). |
| Standards & Certification | Manufactured in accordance and compliance with MCHW clause 518, BBA HAPAS certificate no (09/H145). Note: BBA Hapas certificate does not apply to plastic pipes over DN900. |
| Performance | MetroDrain have a minimum short term ring stiffness value of SN6, a creep ratio of less than 4 and adequate resistance to static loads. Pipe is to be used in non-adoptable applications. |
| Packaging | Supplied in 6 metre lengths as standard in timber framed packs (quantity of product per packaged unit is dependent upon the external diameter of the product). Sizes DN600 and above are supplied loose. |
| Storage | For long term storage keep away from direct sunlight to avoid product degradation, over 12 months exposure to direct sunlight should be avoided. |

| MetroDrain Solid Pipes | | | | | | | |
|------------------------|---------------|---------------------------------|---------|---------|------------|---------------|----------|
| Product ID | Product Range | Accreditation/ Certification | ID (mm) | OD (mm) | Length (m) | Weight (kg/m) | Pack Qty |
| 71302 | Plain Ended | BBA | 150 | 173 | 6 | 1.4 | 33 |
| 71303 | Plain Ended | BBA | 225 | 265 | 6 | 3 | 14 |
| 71304 | Plain Ended | BBA | 300 | 353 | 6 | 5 | 9 |
| 71305 | Plain Ended | BBA | 375 | 432 | 6 | 7.4 | 5 |
| 71306 | Plain Ended | BBA | 450 | 518 | 6 | 10.8 | 4 |
| 71307 | Plain Ended | BBA | 600 | 692 | 6 | 18.6 | 28/load |
| 71308 | Plain Ended | BBA | 750 | 860 | 6 | 26.8 | 18/load |
| 71311 | Socketed | BBA | 750 | 918 | 6 | 26.8 | 18/load |
| 71309 | Plain Ended | BBA | 900 | 1034 | 6 | 36 | 8/load |
| 71321 | Socketed | BBA | 900 | 1093 | 6 | 36 | 8/load |
| 71310 | Plain Ended | | 1050 | 1190 | 6 | 51.2 | 8/load |
| 71328 | Socketed | | 1050 | 1255 | 6 | 51.2 | 8/load |

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and NAYLOR may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on February 2024. Updates will not be issued automatically.

This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication, you must do so at your own risk. All rights reserved. Copyright in this publication belongs to NAYLOR and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent.

Technical Support

Our dedicated technical team is available for guidance and assistance.

For further information, please contact our Support Team: help@naylor.co.uk

www.naylor.co.uk

